

Package: ggsmc (via r-universe)

October 29, 2024

Type Package

Title Visualising Output from Sequential Monte Carlo Samplers and Ensemble-Based Methods

Version 0.1.2.0

Maintainer Richard G Everitt <richard.g.everitt@gmail.com>

Description Functions for plotting, and animating, the output of importance samplers, sequential Monte Carlo samplers (SMC) and ensemble-based methods. The package can be used to plot and animate histograms, densities, scatter plots and time series, and to plot the genealogy of an SMC or ensemble-based algorithm. These functions all rely on algorithm output to be supplied in tidy format. A function is provided to transform algorithm output from matrix format (one Monte Carlo point per row) to the tidy format required by the plotting and animating functions.

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

URL <https://github.com/richardgeveritt/ggsmc>,
<https://richardgeveritt.github.io/ggsmc/>

BugReports <https://github.com/richardgeveritt/ggsmc/issues>

Imports poorman, ggplot2, gganimate

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

Depends R (>= 2.10)

License MIT + file LICENSE

Repository <https://richardgeveritt.r-universe.dev>

RemoteUrl <https://github.com/richardgeveritt/ggsmc>

RemoteRef HEAD

RemoteSha 0f3f579b43dcf26ff15b19cd9c184fa0acdda0d3

Contents

animate_density	2
animate_histogram	3
animate_reveal_time_series	5
animate_scatter	6
animate_time_series	8
cwna_data	9
lv_output	9
matrix2tidy	10
mixture_25_particles	10
plot_density	11
plot_genealogy	12
plot_histogram	13
plot_scatter	14
plot_time_series	15
sir_cwna_model	16
Index	18

animate_density	<i>An animated density of a single variable across targets.</i>
-----------------	-----------------------------------------------------------------

Description

An animated density of a single variable across targets.

Usage

```
animate_density(
  output,
  parameter,
  dimension = 1,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE,
  duration = NULL,
  animate_plot = TRUE,
  save_filename = NULL,
  save_path = NULL
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameter	The parameter for which we wish to view the density.
dimension	(optional) The dimension of the parameter for which we wish to view the density. (default is 1)
target	(optional) If specified, will fix to this target, and animate over ExternalTarget (if present in output).
external_target	(optional) If specified, will fix to this external_target, and animate over Target.
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the density. If TRUE, will use the particle weights. (defaults to TRUE)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)
duration	(optional) The duration of the animation. (defaults to producing an animation that uses 10 frames per second)
animate_plot	(optional) If TRUE, will return an animation. If FALSE, returns a gganim object that can be further modified before animating. (defaults to FALSE)
save_filename	(optional) If specified, the animation will be saved to a gif with this filename. (default is not to save)
save_path	(optional) If specified along with save_filename, will save the gif to save_path/save_filename. (defaults to working directory)

Value

An animated density

animate_histogram *An animated histogram of a single variable across targets.*

Description

An animated histogram of a single variable across targets.

Usage

```

animate_histogram(
  output,
  parameter,
  dimension = 1,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  bins = 30,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE,
  duration = NULL,
  animate_plot = TRUE,
  save_filename = NULL,
  save_path = NULL
)

```

Arguments

<code>output</code>	Output from the SMC or EnK algorithm.
<code>parameter</code>	The parameter we wish to histogram.
<code>dimension</code>	(optional) The dimension of the parameter we wish to histogram. (default is 1)
<code>target</code>	(optional) If specified, will fix to this target, and animate over ExternalTarget (if present in output).
<code>external_target</code>	(optional) If specified, will fix to this external_target, and animate over Target.
<code>use_initial_points</code>	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
<code>use_weights</code>	(optional) If FALSE, will ignore particle weights in the histogram. If TRUE, will use the particle weights. (defaults to TRUE)
<code>bins</code>	(optional) Number of bins for the histogram. (default 30)
<code>xlimits</code>	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
<code>ylimits</code>	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
<code>default_title</code>	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)
<code>duration</code>	(optional) The duration of the animation. (defaults to producing an animation that uses 10 frames per second)
<code>animate_plot</code>	(optional) If TRUE, will return an animation. If FALSE, returns a gganim object that can be further modified before animating. (defaults to FALSE)
<code>save_filename</code>	(optional) If specified, the animation will be saved to a gif with this filename. (default is not to save)
<code>save_path</code>	(optional) If specified along with save_filename, will save the gif to save_path/save_filename. (defaults to working directory)

Value

An animated histogram

animate_reveal_time_series

Plot animated line graph showing parameter value vs dimension (revealed in the animation) from algorithm output.

Description

Plot animated line graph showing parameter value vs dimension (revealed in the animation) from algorithm output.

Usage

```
animate_reveal_time_series(  
  output,  
  parameters,  
  target = NULL,  
  external_target = NULL,  
  use_initial_points = TRUE,  
  use_weights = TRUE,  
  max_line_width = 1,  
  alpha = 0.1,  
  xlimits = NULL,  
  ylimits = NULL,  
  duration = NULL,  
  animate_plot = TRUE,  
  save_filename = NULL,  
  save_path = NULL  
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameters	The parameters we wish to be on the y-axis of the line graph.
target	(optional) The target to plot. (default is to use all targets)
external_target	(optional) The external target to plot. (default is to use all external targets, or to ignore if the column is not present)
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the line graph. If TRUE, will use the particle weights. (defaults to TRUE)

max_line_width	(optional) The maximum size of the points in the plot. (default=1)
alpha	(optional) The transparency of the lines in the plot. (default=0.1)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
duration	(optional) The duration of the animation. (defaults to producing an animation that uses 10 frames per second)
animate_plot	(optional) If TRUE, will return an animation. If FALSE, returns a gganim object that can be further modified before animating. (defaults to FALSE)
save_filename	(optional) If specified, the animation will be saved to a gif with this filename. (default is not to save)
save_path	(optional) If specified along with save_filename, will save the gif to save_path/save_filename. (defaults to working directory)

Value

An animated line graph, which successively adds points along the time axis.

animate_scatter	<i>A histogram of a single variable from a single target.</i>
-----------------	---------------------------------------------------------------

Description

A histogram of a single variable from a single target.

Usage

```
animate_scatter(
  output,
  x_parameter,
  x_dimension,
  y_parameter,
  y_dimension,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  max_size = 1,
  alpha = 0.1,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE,
  view_follow = FALSE,
  shadow_mark_proportion_of_max_size = NULL,
  shadow_wake_length = NULL,
  duration = NULL,
```

```

    animate_plot = TRUE,
    save_filename = NULL,
    save_path = NULL
)

```

Arguments

output	Output from the SMC or EnK algorithm.
x_parameter	The parameter indexed by the x-axis.
x_dimension	(optional) The dimension of the x-parameter we wish to histogram. (default is 1)
y_parameter	The parameter indexed by the y-axis.
y_dimension	(optional) The dimension of the y-parameter we wish to histogram. (default is 1)
target	(optional) If specified, will fix to this target, and animate over ExternalTarget (if present in output).
external_target	(optional) If specified, will fix to this external_target, and animate over Target.
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the scatter plot. If TRUE, will use the particle weights. (defaults to TRUE)
max_size	(optional) The maximum size of the points in the plot. (default=1)
alpha	(optional) The transparency of the points in the plot. (default=0.1)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)
view_follow	(optional) If TRUE, the view will follow the particles. (default FALSE)
shadow_mark_proportion_of_max_size	(optional) If set, the animation will leave behind shadow points, of a size (and transparency) specified by this proportion. (default to not set)
shadow_wake_length	(optional) If set, the animation will leave a shadow wake behind each point, of a duration given by this parameter (proportion of the entire animation length). (default to not set)
duration	(optional) The duration of the animation. (defaults to producing an animation that uses 10 frames per second)
animate_plot	(optional) If TRUE, will return an animation. If FALSE, returns a gganim object that can be further modified before animating. (defaults to FALSE)
save_filename	(optional) If specified, the animation will be saved to a gif with this filename. (default is not to save)
save_path	(optional) If specified along with save_filename, will save the gif to save_path/save_filename. (defaults to working directory)

Value

A scatter plot in a ggplot figure.

animate_time_series	<i>Plot animated line graph showing parameter value vs dimension across targets from algorithm output.</i>
---------------------	------------------------------------------------------------------------------------------------------------

Description

Plot animated line graph showing parameter value vs dimension across targets from algorithm output.

Usage

```
animate_time_series(  
  output,  
  parameters,  
  target = NULL,  
  external_target = NULL,  
  use_initial_points = TRUE,  
  use_weights = TRUE,  
  max_line_width = 1,  
  alpha = 0.1,  
  xlimits = NULL,  
  ylimits = NULL,  
  duration = NULL,  
  animate_plot = TRUE,  
  save_filename = NULL,  
  save_path = NULL  
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameters	The parameters we wish to be on the y-axis of the line graph.
target	(optional) The target to plot. (default is to use all targets)
external_target	(optional) The external target to plot. (default is to use all external targets, or to ignore if the column is not present)
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the line graph. If TRUE, will use the particle weights. (defaults to TRUE)
max_line_width	(optional) The maximum size of the points in the plot. (default=1)

alpha	(optional) The transparency of the lines in the plot. (default=0.1)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
duration	(optional) The duration of the animation. (defaults to producing an animation that uses 10 frames per second)
animate_plot	(optional) If TRUE, will return an animation. If FALSE, returns a gganim object that can be further modified before animating. (defaults to FALSE)
save_filename	(optional) If specified, the animation will be saved to a gif with this filename. (default is not to save)
save_path	(optional) If specified along with save_filename, will save the gif to save_path/save_filename. (defaults to working directory)

Value

An animated line graph, showing how the lines evolve through the sequence of targets.

cwna_data	<i>Data generated from a constant velocity (or continuous white noise acceleration, CWNA) model for 20 time steps.</i>
-----------	------------------------------------------------------------------------------------------------------------------------

Description

Data generated from a constant velocity (or continuous white noise acceleration, CWNA) model for 20 time steps.

Usage

cwna_data

Format

20 observations of 4 variables.

lv_output	<i>10000 simulations from a stochastic Lotka-Volterra model, assigned weights according to a Gaussian approximate Bayesian computation kernel with tolerance equal to 50.</i>
-----------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

10000 simulations from a stochastic Lotka-Volterra model, assigned weights according to a Gaussian approximate Bayesian computation kernel with tolerance equal to 50.

Usage

```
lv_output
```

Format

320000 observations of 15 variables.

matrix2tidy	<i>Convert IS, SMC or EnK output stored as a matrix to tidy format.</i>
-------------	-------------------------------------------------------------------------

Description

Convert IS, SMC or EnK output stored as a matrix to tidy format.

Usage

```
matrix2tidy(output, parameter, target = 1, log_weights = NULL)
```

Arguments

output	Matrix output (one point per row) from an IS algorithm, or one target from a SMC or EnK algorithm.
parameter	The name to assign the parameter in the tidy output.
target	(optional) The target index to use in the tidy output (default 1).
log_weights	(optional) The log_weights to use in the tidy output (default all equal).

Value

The output in tidy format.

mixture_25_particles	<i>The output of an SMC sampler where the initial distribution is a Gaussian and the final target is a mixture of Gaussians. 25 particles were used, with an adaptive method to determine the sequence of targets, and a Metropolis-Hastings move to move the particles at each step.</i>
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

The output of an SMC sampler where the initial distribution is a Gaussian and the final target is a mixture of Gaussians. 25 particles were used, with an adaptive method to determine the sequence of targets, and a Metropolis-Hastings move to move the particles at each step.

Usage

```
mixture_25_particles
```

Format

175 observations of 13 variables.

plot_density	<i>A density of a single variable.</i>
--------------	----------------------------------------

Description

A density of a single variable.

Usage

```
plot_density(
  output,
  parameter,
  dimension = 1,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameter	The parameter for which we wish to view the density.
dimension	(optional) The dimension of the parameter for which we wish to view the density. (default is 1)
target	(optional) The index of the target for which we wish to view the density. (default to all targets)
external_target	(optional) The index of the external target to plot. (default is to use all external targets, or to ignore if the column is not present)
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the density. If TRUE, will use the particle weights. (defaults to TRUE)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)

Value

A density in a ggplot figure.

plot_genealogy	<i>Plot an SMC or EnK genealogy from algorithm output.</i>
----------------	------------------------------------------------------------

Description

Plot an SMC or EnK genealogy from algorithm output.

Usage

```
plot_genealogy(  
  output,  
  parameter,  
  dimension = 1,  
  target = NULL,  
  external_target = NULL,  
  use_initial_points = TRUE,  
  use_weights = TRUE,  
  alpha_points = 0.1,  
  alpha_lines = 0.1,  
  axis_limits = NULL,  
  vertical = TRUE,  
  arrows = TRUE,  
  default_title = FALSE  
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameter	The parameter we wish to see the evolution of.
dimension	(optional) The dimension of the parameter we wish to see the evolution of. (default is 1)
target	(optional) The target to plot. (default is to use all targets)
external_target	(optional) The external target to plot. (default is to use all external targets, or to ignore if the column is not present)
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the line graph. If TRUE, will use the particle weights. (defaults to TRUE)
alpha_points	(optional) The transparency of the points in the plot. (default=0.1)

alpha_lines	(optional) The transparency of the lines in the plot. (default=0.1)
axis_limits	(optional) Input of the form c(start,end), which specifies the ends of the parameter axis.
vertical	(optional) If TRUE (default), plots a genealogy vertically. If FALSE, plots horizontally.
arrows	(optional) If TRUE (default), includes arrowheads. If FALSE, arrowheads are omitted.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)

Value

A particle genealogy in a ggplot figure.

plot_histogram	<i>A histogram of a single variable.</i>
----------------	------------------------------------------

Description

A histogram of a single variable.

Usage

```
plot_histogram(
  output,
  parameter,
  dimension = 1,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  bins = 30,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE
)
```

Arguments

output	Output from the SMC or EnK algorithm.
parameter	The parameter we wish to histogram.
dimension	(optional) The dimension of the parameter we wish to histogram. (default is 1)
target	(optional) The index of the target we wish to histogram. (default to all targets)
external_target	(optional) The index of the external target to plot. (default is to use all external targets, or to ignore if the column is not present)

use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the histogram. If TRUE, will use the particle weights. (defaults to TRUE)
bins	(optional) Number of bins for the histogram. (default 30)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)

Value

A histogram in a ggplot figure.

plot_scatter

A histogram of a single variable from a single target

Description

A histogram of a single variable from a single target

Usage

```
plot_scatter(
  output,
  x_parameter,
  x_dimension = 1,
  y_parameter,
  y_dimension = 1,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  max_size = 1,
  alpha = 0.1,
  xlimits = NULL,
  ylimits = NULL,
  default_title = FALSE
)
```

Arguments

output	Output from the SMC or EnK algorithm.
x_parameter	The parameter indexed by the x-axis.
x_dimension	(optional) The dimension of the x-parameter we wish to histogram. (default is 1)
y_parameter	The parameter indexed by the y-axis.
y_dimension	(optional) The dimension of the y-parameter we wish to histogram. (default is 1)
target	(optional) The index of the target we wish to plot. (default is to use all targets)
external_target	(optional) The index of the external target to plot. (default is to use all external targets, or to ignore if the column is not present)
use_initial_points	(optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)
use_weights	(optional) If FALSE, will ignore particle weights in the scatter plot. If TRUE, will use the particle weights. (defaults to TRUE)
max_size	(optional) The maximum size of the points in the plot. (default=1)
alpha	(optional) The transparency of the points in the plot. (default=0.1)
xlimits	(optional) Input of the form c(start,end), which specifies the ends of the x-axis.
ylimits	(optional) Input of the form c(start,end), which specifies the ends of the y-axis.
default_title	(optional) If TRUE, will provide a default title for the figure. If FALSE, no title is used. (defaults to FALSE)

Value

A scatter plot in a ggplot figure.

plot_time_series	<i>Plot line graph showing parameter value vs dimension from algorithm output.</i>
------------------	------------------------------------------------------------------------------------

Description

Plot line graph showing parameter value vs dimension from algorithm output.

Usage

```
plot_time_series(
  output,
  parameters,
  target = NULL,
  external_target = NULL,
  use_initial_points = TRUE,
  use_weights = TRUE,
  max_line_width = 1,
  alpha = 0.1,
  xlimits = NULL,
  ylimits = NULL
)
```

Arguments

output Output from the SMC or EnK algorithm.

parameters The parameters we wish to be on the y-axis of the line graph.

target (optional) The target to plot. (default is to use all targets)

external_target (optional) The external target to plot. (default is to use all external targets, or to ignore if the column is not present)

use_initial_points (optional) If target is not specified and this argument is TRUE, will add the initial unweighted proposed points to the output to be plotted. (default is TRUE)

use_weights (optional) If FALSE, will ignore particle weights in the line graph. If TRUE, will use the particle weights. (defaults to TRUE)

max_line_width (optional) The maximum size of the points in the plot. (default=1)

alpha (optional) The transparency of the lines in the plot. (default=0.1)

xlimits (optional) Input of the form c(start,end), which specifies the ends of the x-axis.

ylimits (optional) Input of the form c(start,end), which specifies the ends of the y-axis.

Value

A line graph in a ggplot figure.

sir_cwna_model	<i>The output of a bootstrap particle filter on the cwna_data. The output consists of 100 particles over 20 time steps.</i>
----------------	-----------------------------------------------------------------------------------------------------------------------------

Description

The output of a bootstrap particle filter on the cwna_data. The output consists of 100 particles over 20 time steps.

sir_cwna_model

17

Usage

`sir_cwna_model`

Format

4000 observations of 13 variables.

Index

* datasets

- cwna_data, 9
- lv_output, 9
- mixture_25_particles, 10
- sir_cwna_model, 16

- animate_density, 2
- animate_histogram, 3
- animate_reveal_time_series, 5
- animate_scatter, 6
- animate_time_series, 8

- cwna_data, 9

- lv_output, 9

- matrix2tidy, 10
- mixture_25_particles, 10

- plot_density, 11
- plot_genealogy, 12
- plot_histogram, 13
- plot_scatter, 14
- plot_time_series, 15

- sir_cwna_model, 16